

## M.2 2280 SSD

### IM2S3338



The ADATA IM2S3338 M.2 2280 SSD is equipped with 96-layer 3D TLC (BiCS4) NAND flash for excellent read/write performance and high capacities. Its 3K P/E cycle rating ensures long-lasting durability. What's more, with LDPC ECC error correction and RAID Engine, the IM2S3338 ensures data accuracy and integrity. The SSD comes in a range of capacities for different requirements. Customers can also benefit from ADATA's proprietary A+ SDDTOOL software for easy management and real-time monitoring of ADATA SSDs. The IM2S3338 is ideal for automation, embedded system, networking, surveillance and transportation applications.

### Features

- 96-layer 3D TLC (BiCS4) NAND flash for high capacities and efficiency
- 3K P/E cycle rating for excellent durability and reliability
- Low power consumption: 2.0W
- LDPC ECC error correction, RAID Engine, and DRAM Buffer
- Thermal Throttling automatically adjusts temperatures for prolonged product lifespan
- Suitable for automation, embedded system, networking, surveillance and transportation applications


### Ordering Information

Operating Temp.	64GB	128GB	256GB	512GB	1TB
0°C to 70°C	IM2S3338-064GD	IM2S3338-128GD	IM2S3338-256GD	IM2S3338-512GD	IM2S3338-001TD

**Specifications**

Model	IM2S3338
Form Factor	M.2 2280
Capacity	64GB –1TB
Interface	SATA III
Flash Type	96L 3D TLC
Dimensions (L x W x H)	80 x 22 x 3.6mm
Sequential Read (Max.)	550MB/s
Sequential Write (Max.)	480MB/s
Operating Temperature	0°C to 70°C
Operating Voltage	3.3V
Power Consumption (Max.)	2.0W
Shock Resistance	1500G/0.5ms, Half Sine Wave
Operating Humidity	5%-95% RH, non-condensing
Vibration Resistance	20G (20-2000Hz)
Technologies	LDPC ECC, RAID Engine, Wear Leveling, SLC Cache, DRAM Buffer, TRIM and NCQ command, Thermal Throttling, S.M.A.R.T. Monitor

**Diagram**



**Contact Us**

**HQ (Taiwan):**

T: +886-8228-0886

E: [adata@adata.com](mailto:adata@adata.com)

**US:**

T: +1-714-332-8708

E: [IASales\\_us@adata.com](mailto:IASales_us@adata.com)

**EU:**

T: +49-899-0405-296

E: [IASales\\_eu@adata.com](mailto:IASales_eu@adata.com)

**China**

T: +86-21-6233-1010

E: [IASales\\_cn@adata.com](mailto:IASales_cn@adata.com)

**JP:**

T: +81-3-5807-0011

E: [IASales\\_jp@adata.com](mailto:IASales_jp@adata.com)

**APAC/MEA:**

E: [IASales\\_apacmea@adata.com](mailto:IASales_apacmea@adata.com)